



MAIN FLOOR PLAN
SCALE 3/32"=1'-0"

WALL SCHEDULE

- 1 SPRUNG SHIELD or EQUAL (UP TO 10'-0" HT.)
- 2 ARCHITECTURAL HERBERANE R30 FIBERGLASS INSULATION ALUMINUM FRAME (SEE SPRUNG DRAWINGS)
- 3 INTERIOR HERBERANE (UP TO 10'-0" HT.) (SEE SPRUNG DRAWINGS FOR ADDITIONAL INFORMATION)
- 4 SPRUNG SHIELD or EQUAL (UP TO 10'-0" HT.)
- 5 ARCHITECTURAL HERBERANE R30 FIBERGLASS INSULATION ALUMINUM FRAME (SEE SPRUNG DRAWINGS)
- 6 VOID SPACE
- 7 5/8" TYPE 'X' GYPSUM BOARD
- 8 2x6 STUDS @ 16" O.C.
- 9 3/8" PLYWOOD SHEATHING BOARD (UP TO 1H- FIRE RESISTANCE RATING)
- 10 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x6 STUDS @ 16" O.C.
- 11 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 12 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 13 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 14 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 15 1 1/2" GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 16 1 1/2" GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 17 1 1/2" GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 18 1 1/2" GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 19 1 1/2" GYPSUM BOARD 2x4 STUDS @ 16" O.C.
- 20 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x6 STUDS @ 16" O.C.
- 21 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x6 STUDS @ 16" O.C.
- 22 INTERIOR FINISH BOARD (2)-LAYERS OF 5/8" TYPE-X' GYPSUM BOARD 2x6 STUDS @ 16" O.C.
- 23 ARCHITECTURAL HERBERANE R30 FIBERGLASS INSULATION ALUMINUM FRAME (BY SPRUNG or EQUAL)

WOOD WALLS (RATED):

- 1 SPRUNG SHIELD STAIRS ABOVE STADIUM SAVERS
- 2 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 3 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 4 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 5 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 6 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 7 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 8 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 9 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 10 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 11 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 12 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 13 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 14 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 15 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 16 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 17 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 18 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 19 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 20 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 21 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 22 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 23 42" HT. GUARD RAIL (BY STADIUM SAVER)

WOOD WALLS:

- 1 SPRUNG SHIELD STAIRS ABOVE STADIUM SAVERS
- 2 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 3 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 4 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 5 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 6 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 7 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 8 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 9 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 10 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 11 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 12 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 13 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 14 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 15 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 16 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 17 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 18 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 19 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 20 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 21 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 22 42" HT. GUARD RAIL (BY STADIUM SAVER)
- 23 42" HT. GUARD RAIL (BY STADIUM SAVER)

NOTES:

- 1) SEE ALSO GENERAL NOTES FOR FURTHER WALL
 - 2) RATED WALLS SHALL BE FRAMED TO UNDERSIDE OF FLOOR ASSEMBLY OR ROOF DECK, UNLESS NOTED
 - 3) ADD BLOCKING BETWEEN STUDS AS REQUIRED TO SUPPORT ALL EDGES OF 1/2" TYPE 'X' GYPSUM BOARD OR USE 5/8" TYPE 'X' GYPSUM BOARD IN ALL EDGES
 - 4) HIGH TRAFFIC AREAS SHALL BE USED IN FIRE SEPARATIONS SHOWN AS:
- 1 1/2" FIRE SEPARATION
 - 1 Hr FIRE SEPARATION
 - 3/4 Hr FIRE SEPARATION
 - APPROPRIATE THICKNESS
 - INSTALL GYPSUM BOARD OF APPROPRIATE THICKNESS TO MATCH ADJACENT WALL THICKNESS OR OFFSET WALL FRAMING
 - INSTALL FIBRE REINFORCED PLASTIC (FRP) PANEL (BATHROOM/SHOWER SIDE/CONCESSION SIDE)
 - INSTALL 3/4" PLYWOOD SHEATHING (DRESSING ROOM SIDE)

NOTE:

ALL COMPONENTS, FINISHES, MATERIALS, DOORS, WINDOWS, WALL CONSTRUCTIONS, ETC. AS SHOWN HERE SHALL BE APPLIED IN THEIR ENTIRETY TO THE PRE-ENG OPTION AS LAID OUT ON PLAN A2.1a

NOTES

STAIRS

RESTRICTED PRACTITIONER
Registration #1788
Ternance W. Bearden, P. Eng.
Scope of Practice noted on Certificate of Authorization #2001
The Alberta Association of Architects
May 26, 2010

PROFESSIONAL ENGINEER
ALBERTA
Ternance W. Bearden
No. 12345
Professional Engineer
Alberta Association of Engineers
1999

BEARDEN
Engineering Consultants Ltd. (1978)
4842 Riverdale Road, Edmonton, Alberta T6A 1A1
P.O. Box 10000, Edmonton, Alberta T6A 1A1
Tel: (780) 543-8888 Fax: (780) 543-8142 Email: info@bearden.ca

PROJECT NAME
PROPOSED
MAYERTHORPE EXHIBITION CENTRE
ALBERTA

DRAWING TITLE
MAIN FLOOR PLAN

PROJECT NUMBER
09-169

DATE
May 26, 10

SCALE
3/32"=1'-0"

PROJECT NUMBER
09-169

DATE
May 26, 10

SCALE
3/32"=1'-0"

DRAWING NUMBER
A2.1